

TECHNICAL DATA SHEET 2/7				
SMT I	BOARD TO BOAL	Н3	R107.064.920	
REEL OF 100			Series : IMP	
PACKAGINGStandardUnitOther100'W' optionContact us		SPECIFICATION		
ELECTRICAL CHARACTERISTICS			ENVIRONMENTAL	
Impedance Frequency VSWR Insertion loss RF leakage Voltage rating	0-6 1.10 + 0.030 0.2 - (Ω GHz x F(GHz) Maxi √F(GHz) dB Maxi - F(GHz)) dB Maxi Veff Maxi	Operating temper Hermetic seal Panel leakage	rature -40/+90 ° C Atm.cm3/s
Dielectric withstanding voltage350Veff miniInsulation resistance3000MΩ mini			OTHERS CHARACTERISTICS	
			Assembly instruc Others : Weight reel : 75 g	tion
MECHAN	ICAL CHARACTE	RISTICS		
Center contact retent Axial force – Matin Axial force – Oppos Torque	g end	N mini N mini N.cm mini		
Recommended torque Mating Panel nut	2	N.cm N.cm		
Mating life Weight	20 0.020	Cycles mini g		
Issue : 0417 A In the effort to improve necessary.	our products, we reserve	the right to make cha	anges judged to be	RADIALL [®]

TECHNICAL DATA SHEET


SMT BOARD TO BOARD ADAPTOR H3

REEL OF 100

R107.064.920 Series : **IMP**

SOLDER PROCEDURE

- Deposition of solder paste 'Sn Ag4 Cu0.5' on mounting zone by screen printing application. We recommend a low residue flux.
 We advise a thickness of 150 microns (5.850 microinch). Verify that the edges of the zone are clean.
- 2. Placement of the receptacle on the mounting zone with an automatic machine of 'pick and place' type. Video camera is recommended for the positioning of the component. Adhesive agents must not be used on the receptacle.
- 3. This process of soldering has been tested with convection oven. Below please find, the typical profile to use.
- 4. Cleaning of printed circuit boards.
- 5. Checking of solder joints and position of the component by visual inspection.




TEMPERATURE PROFILE

Issue : 0417 A In the effort to improve our products, we reserve the right to make changes judged to be necessary.



3/7






SMT BOARD TO BOARD ADAPTOR H3

REEL OF 100

Series : IMP

R107.064.920



5/7

